

References

- [1] M. W. Bittinger and R. A. Longenbaugh, *Theoretical distribution of water from a moving irrigation sprinkler*, Trans. Amer. Soc. Agric. Eng. 5(1): 26-30, (1962).
- [2] D. F. Heermann and P. R. Hein, *Performance characteristics of self-propelled center pivot sprinkler irrigation system*, Trans, ASAE, 11(1), 11-15, (1968).
- [3] R. G. Evans, S. Han, L. G. James and M. W. Kroeger, *CPIMA computer simulation program for center pivot irrigation systems*; ASAE Paper No. 93-3065. St. Joseph, MI, USA: ASAE. (1993)
- [4] B. Bremond and B. Molle, *Characterization of rainfall under center-pivot: influence of measuring procedure". Journal of Irrigation and Drainage Engineering*: ASCE, 121(5): 347–353, (1995).
- [5] D. F. Heermann and K. Stahl, *Center pivot evaluation and design package (CPED) – Users' manual*, Ft. Collins, CO, USA: USDA-ARS-NPA-WMU, (2004)
- [6] M. S. Babel, A. D. Gupta & D. K. Nayak, *A model for optimal allocation of water to competing demands*, Water resources management 19: 693 – 712, (2005)
- [7] A. V. M. Ines, K. Honda, A. D. Gupta, P. Droogers, R.S. Clemnte, *Combining remote sensing simulation modeling and GA optimization to explore water management options in irrigated agriculture. Agricultural water management*, 83. Elsevier Science Publications (2006)
- [8] R. M. Bagher and J. Pyman, *Water delivery optimization program, of Jiroft dam irrigation networks by using GA*, Int. J. Advance. Soft Comput. Appl., Vol 1, No.2. (2009).
- [9] N. Shutze, T. Wohling, M. D. Paly and G. H. Schmitz, *Applications of Evolutionary Computing, Evo-Workshops 2009*: Germany, April 15-17, Proce; 01/(2009).
- [10] M. S. Pais, J. C. Ferreira, M. B. Teixeira, K. Yamanaka, and G. A. Carrijo, *Cost optimization of localized irrigation system using Genetic algorithm*. 11th International Conference, Paisley, UK, September 1-3, Proceedings. Intelligent Data Engineering and Automated Learning – IDEAL (2010)
- [11] L. Tran, S. Schilizzi, M. Chalakov, and R. Kingwell, *Managing multiple use resources: optimizing reservoir water use for irrigation and fisheries*, 55th Annual AARES National Conference, Melbourne, Victoria, Feb (2011).
- [12] I. Mtolera, L. Haibin, L. Ye, S. B. Feng, D. Xue, and M. Yi, *Optimization of tree pipe network layout and size, using Particle swarm optimization*. WSEAS Transaction on Computers. Vol 13 (2014).
- [13] D. G. Yoo, H. M. Lee, A. Sadollah, & J. Kim, H. *Optimal Pipe Size Design for Looped Irrigation Water Supply*, The Scientific World J. V 2015, Article 651763, 10 pages <http://dx.doi.org/10.1155/2015/651763> (2015).
- [14] A. Coppola, G. Dragonetti, A. Sengouga, N. Lamaddalena, A. Comegna, A. Basile, N. Noviello, and L. Nardella, *Identifying Optimal Irrigation Water Needs at District Scale by Using a Physically Based Agro-Hydrological Model*, Water 2019, 11, 841 P:1:25 (2019)