

























14. Luo, C. R. , 1993 "Hydrodynamic Characteristics in Non-uniform Channels "Asian Institute of Technology, Thailand, Dissertation of Doctor of Engineering, WA93-1.
15. Federico, I., Marrone, S., Colagrossi, A., Aristodemo, F., & Veltri, P. (2010). "Simulation of hydraulic jump through sph model". IDRA XXXII Italian Conference of Hydraulics and Hydraulic Construction. Palermo, Italy.
16. Chanson, H., and Brattberg, T.,2000. "Experimental study of the air-water shear flow in a hydraulic jump."Int. J. Multiphase Flow, 26, pp. 583–607.
17. Lennon, J. M and Hill, D. F. "Particle Image Velocity Measurements of Undular and Hydraulic Jumps" Journal of Hydraulic Engineering (ASCE), 2006, pp. 1283-1294.
18. Chanson, H. (2004). The Hydraulics of Open Channel Flow: An Introduction. Oxford Elsevier Ltd.
19. : Mostafa Ali. Abdelaal " Optimum Size of the soil Particles around Bridge Piers in the Curved Channels. Australian Journal of Basic and Applied Sciences, 13(7): 78-84. DOI: 10.22587/ajbas.2019.13.7.12
20. Ahmed Helmy.(2020). "Effect of soil particle size in reducing the Scour around bridge Piers at the Curved Channels". Life Sci J 2020;17(4):43-49]. ISSN: 1097-8135 (Print) / ISSN: 2372-613X (Online).